

Executive Mobile Video Briefcase

DTD-FRC20

Cisco C20-Based Tactical Videoconferencing



- High Definition Mobile VTC solution
- Lightweight attaché form factor just 18 lbs!
- Fully interoperable with all VTC manufacturers
- H.239 graphics sharing included
- 100% Made in USA
- Rear panel I/O and covered storage area
- External camera, video, and audio support
- Detachable HD camera for maximum flexibility
- Meets ALL Airline Carry-On size restrictions

Features

Network Interface:

- 1 x LAN/Ethernet (RJ-45) 10/100/1000

Dual Stream

- H.239 (H.323) dual stream
- BFCP (SIP) dual stream
- Support resolutions up to WXGA (1280 x 768)
- When Dual video stream is activated the main video stream maximum is 720p 30fps

Protocols

- H.323
- SIP

Embedded Encryption

- H.323/SIP point-to-point
- Standards-based: H.235 v2 & v3 and AES
- Automatic key generation and exchange
- Supported in Dual Stream

Performance Features

- Optimal definition up to 1080p30/720p60
- H.323/SIP up to 6 Mbps
- Takes advantage of the Cisco® TelePresence Total Solution, including Cisco TelePresence Multiway, recording and streaming and firewall traversal services

Audio Standards:

G.711, G.722, G.722.1, 64 bit MPEG4 AAC-LD

Audio Inputs (2)

- 1 x 3.5 mm Mic In
- 1 x RCA

Video inputs

- 1 x VGA (for PC graphics input, H.239)
- 1 X HDMI for Camera

Audio Outputs (1)

- 1 x Line Out / Headset (L+R)
- 1 x RCA main audio

Video Outputs (2)

- HDMI Monitor 1
- HDMI Monitor 2

Environmental Data

- Operating temperature: 0°C (32°F) to 40°C (104°F)
- Operating humidity: 15% to 85%, non-condensing
- Storage temperature: -20°C (-4°F) to 60°C (140°F)
- Storage humidity: 10% to 90% non-condensing

Dimensions

• 18 1/2" X 13" X 4 3/4"

Weight

• 18 lbs

Power

• AC Voltage 100-240V, 50-60 Hz, 2.5 A

Warranty

• One year return to factory

For full codec specifications, refer to C20 Quick Set codec data sheet.