

TSG Approved Cisco 7965 VoIP Phone with PoE*

CIS Part Number DTD-7965-TSGB

- Dual Mode 802.af3 PoE* or AC power 110-240VAC power
- Positive Disconnect On-Hook Security
- Headset and Speakerphone enabled
- Class B CNSS5001 Type Acceptance
- Approved optional accessories
- Class 3 PoE device



The CNSS 5001 defined Positive Disconnect feature is manually activated, provides a clear illuminated indication of when the phone audio is active, and engages automatically when the phone is hung up.

TSG On Hook Security Indicator & Activation Switch

Optional Approved Accessories



Cisco 7916 Side Car₁



Headset₂



Push-to-talk Handset₃



AC Power Supply₄

Cisco Quality – TSG-6 Security

Network administrators will appreciate that the CIS modified Cisco IP phones operate normally with all versions of Cisco Unified Communications Manager, Cisco Unified CallManager, and all other network devices providing unrestricted deployment and management. To meet TSG requirements, the soft-key HOLD feature must be disabled at the Call Manager.

The DTD-7965-TSGB is a CNSS 5001 defined Class B certified VoIP telephone. Approved for use in SCIF and SAPF environments, the DTD-7965-TSGB also allows the on-hook security features to be engaged while in a call providing enhanced Hold and Mute security.

*** Some PoE restrictions may apply. Customer environmental variables may present PoE distance limitations.**

Dimensions (H x W x D) 7.5" x 10.5" x 7.5"
Weight 3.0 lbs
Power PoE or 100-240V, 0.5amp, 50 watts – Power supply sold separately
Class 3 PoE device Requires 12 watts power
LAN Port 10/100/1000 RJ45
PC Port 10/100/1000MB RJ45
Operating Temperature 32 to 104°F (0 to 40°C)
Relative Humidity 10 to 95% (non-condensing)
Storage Temperature 14 to 140°F (-10 to 60°C)
Warranty is one year, parts and labor

Approved Accessories

- 1 Mounting stand part # DTD-CP791X-STAND (single)
#DTD-CP791X-STAND (double)
- 2 Headset Plantronics #H91N
- 3 PTT Handset #WS-2620-24
- 4 Power supply DTD-TPES61