



Product Code: DTD-050002

Tactical Universal Power Network UPS Module

Key Features

- One black WAN port (labeled Router)
- One red LAN PoE port (DHCP serviced)
- Two red LAN ports (DHCP serviced)
- One battery backed 19 volt DC output for the black router or satellite terminal
- Four 19 volt* DC auxiliary power connections for laptops or other electronic devices.
- Tested for use with most Dell laptops.

*Different voltages are programmable



This power module becomes the center of a KG-250X encrypted communications system. Enclosed in a ruggedized chassis is a KG-250 (GFE) and red router (for DHCP Service) plus a Power over Ethernet injector. This highly integrated module will operate your communications system from 12 to 24 volts DC, 110 or 220 volts AC or from its internal recharge batteries. The batteries are recharged from any of your input power sources automatically.

Contact Us

CIS Secure Computing
43671 Trade Center Place, Suite 142
Dulles, VA 20166

Phone: 703-996-0500
Fax: 703-996-1111
eFax: fax@cissecure.com
<http://www.cissecure.com>

Specifications

Batteries

19.2 Volt LiFePO4 10AH

Dimensions (H x W x D)

4.0" x 13.0" x 11.0"

Weight

15.0 lbs. (without KG-250X)

Temperatures

Operating: 32 to 140° F (0 to 60° C)

Input Power

12-28 VDC, 95-250 VAC

Warranty

Standard 1 year parts and labor

Optional 3 year parts and labor